


S424A

4U Supports 24-bay SAS3, SATA3 3.5", 2.5"HDD cage 12Gb/s Mini-SAS HD backplane




Key Features


- Support SAS 3.0 12Gb/s, SATA 3.0 6Gb/s interface or backward compatibility.
- Support 6 pcs SFF-8643 internal MH2 mini-SAS HD interface connector for HBA card.
- Built-in front access USB3.0 port
- SATISFICATION- Whenever you have any queries of products, we'll dive right in and find out the root cause and feedback the best solution.











Þ

RoHS



Specifications


M/B	12"x13" E-ATX, SSI
Drive Bays	24x3.5" hot-swap
	Optional(Internal 2.5"x2)
Front Control	Power ON/OFF,UID,USB3.0
	Power Status, HDD Ststus, Fan
Indicators	Status,Lan Activity
Cooling Fans	80x38 (mm) 3 pcs
HDD Backplane	SAS3.0 SATA3.0 x20 Mini SAS
	HDx6(SFF-8643)
Expansion Slots	7x Full Hight
PSU Form Factor	PS2, PS2 Redundant 80Plus
	CRPS 2U 1200W Meet CE Rohs
Material	AL6061, 1.0mm SGCC, ABS-PC
Net Weight	16.2 kg
Gross Weight	19.1kg
Dimensions(DxWxH)	650x431x176(mm)
TOP VIEW	

Motherboards, hard drives, cables and expansion cards are NOT included in chassis.

FRONT VIEW



REAR VIEW



www.izen.tw ⊠info@izen.tw